



RAW CABLE SPECIFICATIONS

AUDIO LINE LEVEL CABLE

PRODUCT	TYPE	NUMBER OF CHANNELS	O.D. INCHES (MM)	AWG	SHIELD TYPE	SHIELD COVERAGE (MINIMUM)	CAP. (PF/FT)	IMPEDANCE (OHMS)	DCR (OHMS/1000 FT)
NK1/6-BLACK	COAXIAL	1	0.235 (5.97)	21	SPIRAL	65%	28	52	12.7
NK2/6-BLACK	TWINAXIAL	1	0.225 (5.72)	24	SPIRAL	95%	19	78	26.91
D-4PR-BLACK	TWISTED PAIR	4	0.340 (8.64)	22	ALUM. TAPE	100%	16	85	16.6
D-8PR-BLACK	TWISTED PAIR	8	0.465 (14.66)	22	ALUM. TAPE	100%	16	85	16.6
D-12PR-BLACK	TWISTED PAIR	12	0.516 (13.11)	22	ALUM. TAPE	100%	16	85	16.6
D-16PR-BLACK	TWISTED PAIR	16	0.605 (15.37)	22	ALUM. TAPE	100%	16	85	16.6
D-20PR-BLACK	TWISTED PAIR	20	0.657 (16.69)	22	ALUM. TAPE	100%	16	85	16.6
D-28PR-BLACK	TWISTED PAIR	28	0.808 (20.52)	22	ALUM. TAPE	100%	16	85	16.6
D-32PR-BLACK	TWISTED PAIR	32	0.842 (21.39)	22	ALUM. TAPE	100%	16	85	16.6
PR-4PR-BLACK	TWISTED PAIR, FT4	4	0.390 (9.91)	24	ALUM. TAPE	100%	24	65	26.5
PR-8PR-BLACK	TWISTED PAIR, FT4	8	0.505 (12.83)	24	ALUM. TAPE	100%	24	65	26.5
PR-12PR-BLACK	TWISTED PAIR, FT4	12	0.600 (15.24)	24	ALUM. TAPE	100%	24	65	26.5
PR-16PR-BLACK	TWISTED PAIR, FT4	16	0.680 (17.27)	24	ALUM. TAPE	100%	24	65	26.5
PR-20PR-BLACK	TWISTED PAIR, FT4	20	0.750 (19.05)	24	ALUM. TAPE	100%	24	65	26.5
PR-28PR-BLACK	TWISTED PAIR, FT4	28	0.870 (22.10)	24	ALUM. TAPE	100%	24	65	26.5
PR-42PR-BLACK	TWISTED PAIR, FT4	42	1.020 (25.91)	24	ALUM. TAPE	100%	24	65	26.5
PR-52PR-BLACK	TWISTED PAIR, FT4	52	1.150 (29.21)	24	ALUM. TAPE	100%	24	65	26.5

AUDIO POWER CABLE

PRODUCT	TYPE	NUMBER OF CONDUCTORS	O.D. INCHES (MM)	AWG	CAP. (PF/FT)	IMPEDANCE (OHMS)	DCR (OHMS PER 1000 FT)
D-16/2-BLACK	PORTABLE	2	0.320 (8.13)	16	39	65	3.99
D-14/2-BLACK	PORTABLE	2	0.320 (8.13)	14	43	55	2.53
D-14/4-BLACK	PORTABLE	4	0.418 (10.62)	14	46	25	2.53
D-14/8-BLACK	PORTABLE	8	0.592 (15.04)	14	38	30	2.53
D-12/2-BLACK	PORTABLE	2	0.369 (9.37)	12	46	50	1.64
D-12/4-BLACK	PORTABLE	4	0.480 (12.19)	12	49	25	1.64
DSC-18/2-GREY	INSTALL, FT4	2	0.196 (4.98)	18	27	70	7.15
DSC-16/2-GREY	INSTALL, FT4	2	0.235 (5.97)	16	28	70	4.39
DSC-14/2-GREY	INSTALL, FT4	2	0.303 (7.70)	14	27	70	2.52
DSC-12/2-GREY	INSTALL, FT4	2	0.379 (9.63)	12	40	60	1.82

THESE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE